



Compressible Flow TME085

One-Dimensional Steady Flow

Flow with Friction

Division of Fluid Dynamics
Department of Mechanics and Maritime Sciences
Chalmers University of Technology

Governing Equations

The starting point is the governing equations for one-dimensional steady-state flow

Continuity

$$\rho_1 u_1 = \rho_2 u_2 \quad (1)$$

Momentum

$$\rho_1 u_1^2 + p_1 - \bar{\tau}_w \frac{bL}{A} = \rho_2 u_2^2 + p_2 \quad (2)$$

where $\bar{\tau}_w$ is the average wall-shear stress

$$\bar{\tau}_w = \frac{1}{L} \int_0^L \tau_w dx \quad (3)$$

b is the tube perimeter, and L is the tube length. For circular cross sections

$$\frac{bL}{A} = \left\{ A = \frac{\pi D^2}{4}, b = \pi D \right\} = \frac{4L}{D}$$

and thus

$$\rho_1 u_1^2 + p_1 - \frac{4}{D} \int_0^L \tau_w dx = \rho_2 u_2^2 + p_2 \quad (4)$$

Energy

$$h_1 + \frac{1}{2} u_1^2 = h_2 + \frac{1}{2} u_2^2 \quad (5)$$

Differential Form

In order to remove the integral term in the momentum equation, the governing equations are written in differential form

Continuity

$$\rho_1 u_1 = \rho_2 u_2 = \text{const} \Rightarrow$$

$$\frac{d}{dx}(\rho u) = 0 \quad (6)$$

Momentum

$$(\rho_2 u_2^2 + p_2 - \rho_1 u_1^2 + p_1) = -\frac{4}{D} \int_0^L \tau_w dx \Rightarrow$$

$$\frac{d}{dx}(\rho u^2 + p) = -\frac{4}{D} \tau_w \quad (7)$$

$$\frac{d}{dx}(\rho u^2 + p) = \rho u \frac{du}{dx} + u \frac{d}{dx}(\rho u) + \frac{dp}{dx} = \left\{ \frac{d}{dx}(\rho u) = 0 \right\} = \rho u \frac{du}{dx} + \frac{dp}{dx}$$

$$\rho u \frac{du}{dx} + \frac{dp}{dx} = -\frac{4}{D} \tau_w \quad (8)$$

The wall shear stress is often approximated using a shear-stress factor, f , according to

$$\tau_w = f \frac{1}{2} \rho u^2 \quad (9)$$

and thus

$$\rho u \frac{du}{dx} + \frac{dp}{dx} = -\frac{2}{D} f \rho u^2 \quad (10)$$

Energy

$$h_1 + \frac{1}{2}u_1^2 = h_2 + \frac{1}{2}u_2^2 = \text{const}$$

$$h_{o1} = h_{o2} = \text{const}$$

$$\frac{d}{dx}h_o = 0 \tag{11}$$

Summary

continuity:

$$\frac{d}{dx}(\rho u) = 0$$

momentum:

$$\rho u \frac{du}{dx} + \frac{dp}{dx} = -\frac{2}{D}f\rho u^2$$

energy:

$$\frac{d}{dx}h_o = 0$$